

# bikeBOX24

## Safety Instructions

The bikeBOX24 must be installed on a straight and level fixed surface. (e.g. concrete, paving stones, walkway plates, tarmac etc. NOT possible: sand, gravel, split, natural ground etc.)

Make sure that you have enough free space of at least 3 meters (10feet). The lid will open up to 3m/10ft!

### CAUTION!

Pay full attention to your surroundings when opening and closing the lid, objects and persons can be caught by the lid, injury may occur.

### CAUTION!

Do not keep the bikeBOX24 open during strong winds! Close the lid immediately after use and make sure it is securely locked!

## Application

Drive or push your motorcycle into the bikeBOX24 by sitting on the bike. If your motorcycle front tire is properly secured in the Steady-Stand fixed no main or kick stand is required.

Just ride the bike with the front wheel over the rocker of the Steady-Stand (motorcycle fixation), the motorcycle becomes securely fixed by dead weight. The Steady-Stand is individually adjustable for 14 "to 21" front wheels and according to your vehicle length in different positions mountable.

Customers who owns a trailer are responsible of proper lashing for the vehicles before, during and after the journey and should check these several times and adjust, if necessary. In addition, the application- and safety instructions of the Trailer Manufacturer and the General Traffic Rules have to be strictly followed too.

## Care and Maintenance Instruction

The bikeBOX24 has a multilayer base plate (waterproof glued) and a cover made of easy-care and weather-resistant multilayer-High-Tech-plastics. For external cleaning, water can be used in combination with soft/commercial household cleaners or car care products.

### Attention! No use of solvent-based cleaners!

bikeBOX 24 GmbH – Tel.: +49 6136 9168-22 - E-Mail: [info@bikebox24.eu](mailto:info@bikebox24.eu) / [www.bikebox24.eu](http://www.bikebox24.eu)

